



## **BELCAR ENDURANCE CHAMPIONSHIP 2022**

### **ADDENDUM 1**

#### **BELCAR BALANCE OF PERFORMANCE**

Version: **01**

Valid from : 20-06-2022

The Balance of Performance Decisions are taken by the promoter of the championship in accord with RACB Sport.

All cars mentioned in the following Tables of this document must comply with this BoP with immediate application starting from the date of publication of this document. This validity will only be cancelled by a newer BoP addendum.

These Balance of Performance decisions are not subject to appeal.

VISA RACB: T01-BELCAR/B22-ADD1



**Table 1 : BOP BELCAR GTa**

| Car  | Min. Ride Height * <sup>1</sup> | Minimum Weight * <sup>2</sup>                                   | Restrictor             | Max. camber static                      |
|--|---------------------------------|---|------------------------|---|
| Audi R8 LMS GT2 <sup>5</sup>   | 90 mm                           | 1350 kg   | 2x 60 mm* <sup>3</sup> | Front : -3,5°<br>Rear : -3°             |
| Lamborghini Super Trofeo & Super Trofeo EVO (2015-2021) <sup>6</sup> | 75 mm                           | 1270 kg without homol. silencer<br>1280 kg with homol. silencer | 2x 41 mm* <sup>4</sup> | Front: -3,0°<br>Rear: -3,0°             |
| Lamborghini Super Trofeo EVO 2 (2022-) <sup>6</sup>                  | 75 mm                           | 1250 kg without homol. silencer<br>1265 kg with homol. silencer | 2x 41 mm* <sup>4</sup> | Front: -3,0°<br>Rear: -3,0°             |
| Porsche 992 GT3 Cup <sup>7</sup>                                     | Front: 72 mm<br>Rear: 106 mm    | 1293 kg   | N/A                    | Front: 19 mm shims<br>Rear: 13 mm shims |
| Porsche 991.2 GT3 Cup <sup>7</sup>                                   | Front: 78 mm<br>Rear: 100 mm    | 1230 kg   | N/A                    | Front: 18 mm shims<br>Rear: 15 mm shims |

\*1: Ride height must be measured according to the homologation of the car and Technical Regulations of the related Series (for Cup cars). If this measurement results in lower ground clearance than the one indicated in Belcar Endurance Technical Regulations Art. 3.4, the latter must be respected.

\*2: This is the weight of the car at any given moment during the meeting, without pilot and his equipment, with an empty fuel tank and the other tanks for different fluids at their normal level.

\*3: The restrictor(s) must conform to SRO GT2 homologation /Technical Regulations, made of metal or metal alloy, 3 mm long and must be entirely visible once the bonnet is open and without dismounting any element or cover.

\*4: Restrictors must be the official Lamborghini part n° 4TA129640

\*5: Car must conform to its GT2 homologation form

\*6: Car must conform to the Technical Regulations of the Super Trofeo Series

\*7: Car must conform to Porsche Endurance Trophy Benelux & Porsche Carrera Cup Benelux Regulations